PRODUCT LINE COMPARISON



PRODUCT:	25G5	2SGSEFI	ILD01	ILD02	CROSS LINER	CROSS LINER LITE	eCROSS LINER
Engine:	Kawasaki FS691V	Kawasaki FS730V-EFI	Kawasaki FS541V	Kawasaki FS691V	Honda GXV390	Honda GXV390	Permanent magnet AC motor
Performance:	P24 HP / 17.9kW	25.5 HP / 19.0kW	18 HP / 13.4kW	24 HP / 17.9kW	10.2 HP / 7.6 kW	10.2 HP / 7.6 kW	1500 W
Displacement:	726 ccm.	726 ccm.	603 ccm.	726 ccm.	389 ccm.	389 ccm.	N/A
Fuel Tank:	4.2 gal.	4.2 gal.	3.2 gal.	4.2 gal.	1.05 gal.	1.05 gal.	N/A
Fuel:	Unleaded Petrol	Unleaded Petrol	Unleaded Petrol	Unleaded Petrol	Unleaded Petrol	Unleaded Petrol	N/A
Transmission:	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic (SD)	Hydrostatic (M&S)	N/A
Oil Tank:	2.4 gal.	2.4 gal.	1.7 gal.	2.4 gal.	1.05 gal.	1.05 gal.	N/A
Speed:	0 - 5 mph	0 - 5 mph	0 - 3.7 mph	0 - 5 mph	3.7 mph	3 mph	0 - 3.1 mph
Drive:	360°, 4WD	360°, 4WD	360°, 4WD	360°, 4WD	SPIDER-mode	SPIDER-mode	360°, 4WD
Skid-Steering:	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tire Type:	l6 x 6.50-8	6 x 6.50-8	l6 x 6.50-8	16 x 6.50-8	13 × 5-6 (xtrack)	13 × 5-6 (turf)	13 × 5-6 (turf)
Productivity:	1.73 acres/hr.	2.1 acres/hr.	0.74 acres/hr.	1.73 acres/hr.	0.6 acres/hr.	0.5 acres/hr.	0.6 acres/hr.
Fuel Consumption:	0.95 gal/hr.	l gal/hr.	0.65 gal/hr.	0.95 gal/hr.	0.4 gal/hr.	0.4 gal/hr.	N/A
Climbing Ability:	55°*	60° *	55° *	55°*	55°	35°	35°
Hydraulic Winch:	Yes	Yes	Yes	Yes	Yes	No	No
Dimensions:	65 x 56 x 32.5 in.	65 x 56 x 32.5 in.	53 × 47 × 36 in.	65 x 56 x 36 in.	39 x 44 x 24 in.	39 x 44 x 24 in.	44 x 38.6 in.
Gross Weight:	853 lbs.	853 lbs.	635 lbs.	853 lbs.	386 lbs.	360 lbs.	401 lbs.
Cutting Width:	48.5 in. (4 blades)	48.5 in. (4 blades)	31.5 in. (center blade)	48.5 in. (4 blades)	25.6 in.	25.6 in.	25.6 in.
Cutting Height:	3.5-5.5 / 2.8-4.7 in.	3.5-5.5 / 2.8-4.7 in.	2.5-4.5 / 1-3 in.	3.5-5.5 / 2.8-4.7 in.	1.6 - 3.9 in.	1.6 - 3.9 in.	1.6 - 3.9 in.
Clutch:	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Mechanical w/ Brake	Mechanical w/ Brake	N/A